



Ergo Line Combo

Ambient + Hot

Ergo Line Combo is a light weight, but robust, cart for holding and transportation of hot and cold food with GN1/1 capacity. Detachable U-shaped runners offer safe handling, easy cleaning and optimal temperature distribution. Infinitely variable temperature setting is performed via digital displays which indicates when the selected temperature is reached. Other features are adjustable ventilation for optimal moisture control, ergonomic push/pull handles and big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Convection heating is offered as an option.

Outer Measurement

| | |
|---------------|---------|
| Width | 540 mm |
| Height | 1445 mm |
| Depth | 810 mm |

Inner Measurement

| | |
|-------------------------------|--------------|
| Width | 330 mm |
| Height (ambient + hot) | 401 + 561 mm |
| Depth (ambient / hot) | 596 / 553 mm |

Capacity & Weight

| | |
|--|--|
| Capacity | 10 x 1/1GN with 80 mm distance between runners |
| Maximum Loading Capacity / Runner | 9 kg |
| Net Weight | 63 kg |
| Volume (ambient + hot) | 79 + 102 liter |

Features

| | |
|------------------|---|
| Color | Black (RAL 9005) is standard. Red (RAL 3003) and Grey (RAL 7042). Free of charge. |
| Signature | Put your logo on the box or wrap it in your pattern. |

Construction & Electrics

| | |
|--------------------------------|---|
| Interior | Anodized aluminium |
| Rack | Detachable laser cut U-shaped runners in SST |
| Exterior | Fiber glass plastic and aluminum profiles |
| Door Handle | Robust excenter lock. One Grip Handle as an option. |
| Door Opening | 270° with a magnet to keep door at fixed position |
| Top Bumper & Chassi | Stainless Steel. Chassi covered with rubber cladding. |
| Power Connection | 220V-240V / 1 phase / 50-60Hz |

Hot

| | |
|--------------------------|--------------|
| Heating Element | Yes |
| Consumption W/A | 353W / 1,53A |
| Temperature Range | Up to 90°C |

ALTERNATIVE

| | |
|---------------------------|-------------|
| Convection Heating | Option |
| Consumption W/A | 415W / 1,8A |
| Temperature Range | Up to 90°C |

Functions, Safety & Ergonomics

| | |
|-------------------------------|--|
| Digital Display | Yes, with temperature reached indicator |
| Adjustable Ventilation | Yes, open & close to adjust moisture level |
| Tray Stop | Protects from door scratches & trays moving |
| Runner Tilt Stop | Extra safety when loading/unloading the box |
| Classifications | CB, CE, EMC, RoHS, REACH & IP44 |
| Castors (standard) | Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake) |
| Handles | Ergonomic push/pull handles 420mm |
| Extra Loading Spaces | Top bumper keeps extra goods safe on top |

Options

| | | |
|-----------------------------|-------------------------------|--------------------------------|
| Convection Heating | Ø 125mm Chromed Castors | Humidifier |
| Central Brake | Ø 160mm CKN Castors | Customized Spacing for Runners |
| Card Holders A4/A5/A6 | Ø 200mm Chromed Castors | Pressed Runners |
| One Grip Handle | Ø 200mm Foam Filled Castors | Stainless Steel Interior |
| One Grip Handle w. Lock Key | Ø 400mm Cross Country Castors | Stainless Steel Exterior |
| Tow Bars | Ergo Drive+ Motorized Chassi | |

For detailed information of available options please refer to scanbox.se